

AXIS F1015 Sensor Unit

Varifocal lens for flexible surveillance

AXIS F1015 offers flexible viewing angles for highly discreet indoor surveillance. For use with an AXIS F Main Unit, AXIS F1015 provides a 1080p resolution and a varifocal lens that provides a 97° to 52° horizontal field of view. A narrower field of view enables finer details to be captured. In wide mode, more of a scene can be covered. AXIS F1015 also supports Wide Dynamic Range (WDR) – Forensic Capture, ideal for scenes with very bright and dark areas. The sensor unit comes with a 3- or 12-m (10/39 ft.) pre-mounted cable for connection to a main unit. A vari-angle mounting bracket is included.

- > **Flexible, discreet design for indoor use**
- > **Varifocal lens with 1080p resolution**
- > **97° - 52° horizontal field of view**
- > **WDR – Forensic Capture (with AXIS F41/F44 Main Unit)**



AXIS F1015 Sensor Unit

Models	AXIS F1015 3 m / 10 ft. cable: Varifocal AXIS F1015 12 m / 39 ft. cable: Varifocal
Camera	
Image sensor	1/2.8" (effective) progressive scan RGB CMOS
Lens	Fixed iris 2.8-6 mm, F2.0 With AXIS F34/F41/F44 in 1080p: Horizontal field of view: 97° to 52° Vertical field of view: 53° to 30° With AXIS F34/F44 in 720p: Horizontal field of view: 62° to 35° Vertical field of view: 35° to 20°
Resolution	Max. 1920x1200/1080
WDR	WDR – Forensic Capture With AXIS F41: 1080p, 25/30 fps (50/60 Hz) With AXIS F44: 720p, 12.5/15 fps (50/60 Hz)
Minimum illumination	Color: 0.3 lux
Shutter speed	With AXIS F34/F44: HDTV 720p 25/30 fps: 1/28000 s to 2 s 1080p 12.5/15 fps: 1/22500 s to 2 s With AXIS F41: HDTV 1080p 25/30/50/60 fps: 1/143000 s to 2 s WUXGA (1920x1200) 25/30 fps: 1/143000 s to 2 s
Frame rate	Max. 50/60 fps (50/60 Hz)
General	
Casing	Aluminum
Operating conditions	-30 °C to 55 °C (-22 °F to 131 °F) Humidity 10-85% RH (non-condensing)
Storage conditions	-40 °C to 65 °C (-40 °F to 149 °F)
Approvals	ECE R10 rev.04, EN 50121-4, IEC/EN/UL 60950-1, IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-14, IEC 60068-2-30, IEC 60068-2-78, IEC 60529 IP4X, IEC 62236-4, EN 55022 Class B, EN 55024, EN 61000-3-2, EN 61000-3-3, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class B, ICES-003 Class B, VCCI Class B, C-tick AS/NZS CISPR 22 Class B, KCC KN22 Class B, KN24, EN 50581 IEC 60068-2-6, IEC 60068-2-27
Dimensions	69 mm (2 3/4 in) ø 30 mm (1 3/16 in)
Weight	3 m / 10 ft. cable: 120 g (0.26 lb) 12 m / 39 ft. cable: 370 g (0.82 lb)
Required hardware	AXIS F34/F41/F44 Main Unit
Included accessories	Installation Guide AXIS F8201 Vari-angle Mounting Bracket
Optional accessories	AXIS F8203 Fixed Mount Bracket AXIS F8215 Varifocal Bullet Accessory
Warranty	5-year warranty, see axis.com/warranty

Environmental responsibility:

axis.com/environmental-responsibility