

AXIS T93E05 Protective Housing

Unobtrusive housing with compact and slim design

AXIS T93E05 protects AXIS M1113/M1114 cameras where they need to be protected but still unobtrusive. AXIS T93E05 features IP66 protection rating against the ingress of dust and high-pressure water jets. The enclosure materials, in combination with the camera, make the use of a window heater unnecessary. Easy installation with Power over Ethernet, and the cable is protected in the wall mount for tamper protection. Various accessories are available for AXIS T93E05, such as ceiling, wall and column mounts and adapters. AXIS T93E05 comes with a wall mount with an internal cable channel and ball joint.

- > **IP66-rated**
- > **Ease of installation**
- > **Compact design**
- > **One cable installation**



AXIS T93E05 Protective Housing

| | | | |
|-----------------------------|---|--------------------------------------|--|
| Supported cameras | AXIS M1113 AXIS M1114 | | 122 x 95 x 303 mm (4.8 x 3.7 x 11.9 in) |
| Casing | Acrylate, IP66-rated Color: White NCS S 1002-B | Weight | 580 g (1.28 lb) |
| Power | Camera powered by PoE via network cable | Included accessories | Wall mount, sunshield, Installation Guide, Desiccant bag |
| Environment | Indoor/Outdoor | Optional accessories | AXIS T94Q01A Wall Mount AXIS T94R01P Conduit Back Box AXIS T91A47 Pole Mount AXIS T98A16-VE Surveillance Cabinet AXIS Bird Control Spike |
| Operating conditions | -20 °C to 50 °C (-4 °F to 122 °F) Humidity 15-100% RH (condensing) | Warranty | Axis 3-year warranty, see www.axis.com/warranty |
| Approvals | IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-14, IEC 60068-2-27, IEC 60068-2-30, IEC 60068-2-78, IEC 60529 IP66, ISO 4892-2 | Environmental responsibility: | www.axis.com/environmental-responsibility |
| Dimensions | Without sunshield: 109 x 82 x 258 mm (4.3 x 3.2 x 10.1 in) With sunshield: | | |